



FLASH-200SP Super Bright LED Spotlight

FLASH-200SP, spotlight, features tremendous light output, illuminating an area over 800ft (250m) away with 180 lumens of light output from cutting edge CREE LED technology. Easily illuminate plenums, warehouse ceilings, vaults, attics, or any dark areas that requires no nonsense illumination. This spot light is rugged, water proof, rugged waterproof housing with rechargeable batteries. This is a must have for those that demand the very best.

- Super bright, brighter than standard incandescent bulbs
- Light source: Cree XRE Q4 LED life time up to 100,000 hours
- Adjustable light output:
 - high beam – over 180 lumens
 - low beam – over 20 lumens
 - strobe – over 180 lumens
- Illuminating distance [under dark condition]:
 - high beam – over 820 feet (250m)
 - low beam – over 165 feet (50m)
- Rechargeable four AA (1.2V/2000mAH Ni-MH) batteries for high efficiency
- Continuous Runtime (based on 4AA 1.2V/2000mAH Ni-MH batteries):
 - high beam (100% light on) – min 2 hours
- Waterproof
- Drop proof up to 3 feet

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive “No Hassle” warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



N10140

FLASH-200SP Super Bright LED Spotlight

Data Sheet

General Specifications

Maximum light output	High beam – up to 200 lumens Low beam – up to 20 lumens Strobe – up to 200 lumens
Continuous run time	Min. 4 hours (high beam)
Battery	AA rechargeable battery x 4
Product size	170.5 x 184.5 x 88 mm (6.7 x 7.3 x 3.4 inch)
Included accessories	AC Power adaptor, Vehicle Charger, Users Manual, Batteries(installed)



Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0